



# Elo TouchSystems' Touchmonitor Product Range

*Elo offers three complete Series of touchmonitors, distinguished in price and degree of customization and sophistication.*

## 1000 Series

**Elo's 1000 Series** is designed to provide a single-source selection of entry-level monitors, aimed at the fast-changing consumer retail/POS and hospitality/POS markets. The products, while offered at a lower price point, still provide reliable, durable operation.

- The 1000 series is available in 12", 15", 17" and 19" LCD models and includes both serial and USB connections.
- Touchmonitors feature AccuTouch five-wire resistive and IntelliTouch surface wave touch technologies.
- Agency approvals include UL, cUL, FCC, CE and TÜV.

## 3000 Series

**Elo's 3000 Series** of "designed for touch" touchmonitors are focused on a wide variety of markets including retail, hospitality, industrial, gaming/entertainment, and office automation.

- The 3000 Series is available in display sizes from 12" to 19" and includes both serial and USB connections.
- Touch technologies include AccuTouch, CarrollTouch, IntelliTouch, SecureTouch, iTouch, Surface Capacitive and Projected Capacitive.
- Integrated peripheral options include a magnetic stripe reader (MSR), a rear-facing customer display and biometric devices.
- Form factors include desktop, panel mount, rear mount, VESA mount and rack mount.
- New clean cable routing makes cable management easier.
- Specially designed stable base on desktop models can be bolted down.
- Control buttons with "user lock-out" featured on desktop models, remote OSD on chassis models.
- Agency approvals include UL, cUL, FCC, CE and TÜV.

## 5000 Series

**Elo's 5000 Series** of "designed for touch" touchmonitors include monitors with industrial-grade sealing, medical approvals and customization.

- If the standard line of Elo monitors doesn't provide a perfect fit, our product design experts can build you one that does.
- Customized metal, plastic, color matching and logo printing.
- Agency approvals include UL, cUL, FCC, CE and TÜV, drip proof (IEC529/IPX1), UL 2601-1, CE MDD, and others on request.



### Worldwide Headquarters

Tel: + 1 650 361 4700  
Fax: + 1 650 361 4747  
eloinfo@elotouch.com

### European Headquarters

Tel: +32 (0)16 35 21 00  
Fax: +32 (0)16 35 21 01  
elosales@elotouch.com

### Germany / Austria / Switzerland

Tel: +49 89 60822-0  
Fax: +49 89 60822-180  
www.elotouch.de

### France

Tel: +33 1 34 20 23 21  
Fax: +33 1 34 20 23 23  
www.elotouch.com.fr

### UK

Tel: +44 1793 57 33 44  
Fax: +44 1793 57 33 45  
www.elotouch.co.uk

### Ireland

Tel: +353 21 480 8351  
Fax: +353 86 806 8519

### Spain, South Europe

Tel: +34 91 66 30 433  
Fax: +34 91 66 60 409

### Italy

Tel: +39 02 575 762 19  
Fax: +39 02 575 762 00

## Desktop LCDs

Model	Series	Size	Specs				Colour		Touch Technology*				Interface		Comments
			max resolution	viewing angle	contrast ratio	Brightness (Panel) cd/m <sup>2</sup>	beige	grey	Accu-Touch	Intelli-Touch	Carroll-Touch	Surface Capacit.	Serial	USB	
1215L	1000	12"	800x600	140°: 110°	400:1	200		x	x	x			x	x	Most economical 12"
1229L	3000	12"	800x600	120°: 90°	300:1	300		x	x	x	x		x	x	MSR, fingerprint reader, rear facing customer display options
1515L	1000	15"	1024x768	120°: 100°	400:1	250		x	x	x			x	x	Most economical 15"
1526L	5000	15"	1024x768	150°: 130°	450:1	300	x		x				x		Medical approvals, IPX1
1529L	3000	15"	1024x768	150°: 125°	400:1	350	x	x	x	x	x	x	x	x	MSR, fingerprint reader, rear facing customer display options
1715L	1000	17"	1280x1024	140°: 123°	450:1	250		x		x			x	x	Most economical 17"
1725/27L	3000	17"	1280x1024	140°: 140°	450:1	260	x	x	x	x			x	x	DVI option
1915L	1000	19"	1280x1024	140°: 135°	550:1	270		x	x	x			x	x	Most economical 19"
1925/27L	3000	19"	1280x1024	170°: 170°	700:1	300	x	x	x	x			x	x	DVI option
1926L	5000	19"	1280x1024	170°: 170°	700:1	300	x	x	x	x			x	x	Medical approvals, DVI option

## Chassis LCDs (rear mount, panel mount, 19" rack mount)

Model	Series	Size	Specs				Mounting		Touch Technology*						Interface		Comments	
			max resolution	viewing angle	contrast ratio	Brightness (Panel) cd/m <sup>2</sup>	front	rear	Accu-Touch	Intelli-Touch	Secure-Touch	Carroll-Touch	Project. Capacit.	Surface Capacit.	Serial	USB		
1247L	1000	12"	800x600	130°: 105°	500:1	350		x		x						x	x	
1537L	1000	15"	1024x768	120°: 100°	400:1	250		x	x	x						x	x	
1547L	3000	15"	1024x768	150°: 125°	500:1	350	x	x	x	x	x	x	x	x		x	x	19" Rack mount option
1549L	3000	15"	1024x768	170°: 170°	400:1	250		x		x						x	x	Wide viewing angle
1747L	3000	17"	1280x1024	140°: 140°	450:1	260	x	x	x	x	x	x				x	x	19" Rack mount option
1739L	3000	17"	1280x1024	178°: 178°	1500:1	280		x		x		x		x		x	x	Wide viewing angle
1939L	3000	19"	1280x1024	170°: 170°	1000:1	250		x		x		x		x		x	x	Wide viewing angle

## Touchcomputer

Model	Series	Size	Monitor specs				Computer specs								Comments
			max resolution	viewing angle	contrast ratio	Brightness (Panel) cd/m <sup>2</sup>	CPU	Win XP	Win XPe	CE.NET	Storage XP	Storage CE	USB ports	RS-232 ports	
1529L	3000	15"	1024x768	150°: 125°	400:1	350	1 Ghz	x	x	x	40 GB HDD	128 MB CF	4 ext.	2 ext.	MSR, rear facing customer display options

## Chassis CRTs (rear mount)

Model	Series	Size	Specs			Mounting		Touch Technology*		Interface		
			max resolution	refresh rate	dot pitch	front	rear	iTouch touch-on-tube	Serial	USB		
1545C	3000	15"	800X600	85Hz	0.28			X		X	X	X
1745C	3000	17"	1024X768	85Hz	0.27			X		X	X	X
1945C	3000	19"	1024X768	85Hz	0.25			X		X	X	X

\*AccuTouch = five-wire resistive - IntelliTouch = surface wave - iTouch = "touch-on-tube" surface wave - SecureTouch = vandal-resistant surface wave - CarrollTouch = infrared.

This list is not Elo's entire product offering. See our websites for the latest models and specifications.

If you require a product configuration that is not featured here, please contact us.